

Building Better Networks with **ROGUE™** | **aEROS™** Test Suite

NEW



ROGUE Carrier

ROGUE is the modular hardware platform that works seamlessly with aeRos and enables customers to pick and choose the functionality they need. Like aeRos, it is an open system built around you, for both CAPEX and OPEX savings. The Rogue carrier is ruggedly built to withstand testing in the field. It is lightweight, portable, and comes with options for carrying and/or placing it on a surface, with a convenient carrying strap and a “kick-stand”. The integrated inspection capabilities ensure that your connections are completely clean.

Features

- Flexible, open, and modular architecture
- Stand-alone or integrated with any Android or iOS device
- Inspection capable
- USB host and function ports
- Bluetooth and Wi-Fi connectivity
- >8 hours Li-ion battery or AC power
- Lightweight, hand-held, easy to carry to any job



ROGUE Carrier



ROGUE Module

Specifications^a

GENERAL	
Size	23 x 11 x 7 cm (8.8 x 4.3 x 2.8 in)
Weight	0.9 kg (2 lb)
Operating Temperature	-10 °C to +50 °C, 0 to 90 % RH (non-condensing)
Storage Temperature	-20 °C to +60 °C, 0 to 90 % RH (non-condensing)
Power	Rechargeable Li-Ion or AC power adapter
Battery Life	>8 hours continuous testing

Notes:

a. All specifications valid at 23°C ±2°C (73.4°F ±3.6°F) unless otherwise specified.

Ordering Information

DESCRIPTION	AFL NO.
ROGUE Carrier with battery, power supply, and adjustable carry strap	RG-C01
ROGUE Carrier Kickstand	RGA-STND-01



ROGUE Carrier

ROGUE Kickstand

International Sales and Service Contact Information

Available at www.AFLglobal.com/Test/Contacts

