



► Model eHorn

Electronic Horn

Electronic horn with two selectable tones.

Model eHorn is an economical electronic horn capable of producing two high decibel horn tone outputs from the same unit by featuring internal amplification and tone circuitry.

The Type 4X, IP66 housing is molded from glass reinforced polycarbonate plastic, making it resistant to ultra-violet light and ideal for indoor or outdoor use.

Model eHorn can be used as a stand-alone, high output, audible warning device in any application where voice paging is not required.

Typical applications include emergency warning, start and dismissal, general alarm and evacuation.

FEATURES

- Multi-voltage design accepts 24VDC and 120/240VAC
- Produces one of two tones at three SPL (sound pressure levels) Federal Signal horns: 52 & 55/56
- Surface mount standard
- Produces 96 - 117dBA @ 10' depending on tone and voltage
- Type 4X, IP66 Enclosure
- UL and cUL Listed, Marine Rated

| MODEL | VOLTAGE | 52 HORN | | | 55/56 HORN | | |
|----------------------|---------|-------------------|---------------|--------------|-------------------|---------------|--------------|
| | | OPERATING CURRENT | DECIBELS @10' | DECIBELS @1M | OPERATING CURRENT | DECIBELS @10' | DECIBELS @1M |
| eHorn-024 | 24VDC | 0.4 - 3.0A | 100 - 116 | 110 - 116 | 0.24 - 3.3A | 96 - 117 | 106 - 127 |
| eHorn-120-240 | 120VAC | 0.15 - 0.78A | 101 - 114 | 111 - 124 | 0.10 - 0.76A | 98 - 116 | 108 - 126 |
| eHorn-120-240 | 240VAC | 0.03 - 0.40A | 101 - 114 | 111 - 124 | 0.06 - 0.41A | 98 - 116 | 108 - 126 |

